

## Product information sheet

Product number: 0101236030

Date: 08.04.2026

Page: 1/3



## ABC Charger 2430, protection class II

**24 V built-in charger with protection class II for professional use with adjustable charging characteristic for gentle charging of the battery.**

- // For all types of lead batteries
- // Auch in Schutzklasse I erhältlich
- // 15 selectable charging characteristics
- // Complies with DIN 14679:2024-02

The ABC 2430 charger in protection class II: Optimal charging of 24 V batteries with a charging current of 30 A. In addition, a remote display or a temperature sensor (CTS) can be connected. The battery charging is fully automatic and microprocessor-monitored with selectable charging characteristic - thus an optimal and gentle charging is guaranteed.

## Technical Information

CBL connection	No*
Charging current	30 A*
Connector, AC input	Schuko plug (type F)*
Connector Temperature Sensor	Yes*
Output voltage (DC)	24 V*
Power category	1.6 kW*
Protection class	II*
Remote display connection	Yes*
Battery capacity	90 Ah ... 300 Ah
Building main fuse	B16 A/C16 A
Cable length, AC input	1.5 m, 1 mm <sup>2</sup>
Cable length, DC output	2 x 2 m, 6 mm <sup>2</sup>
Charging characteristic	15 selectable charging programmes
Complies with DIN 14679:2024-02	yes
Input frequency range	47 Hz ... 400 Hz
Input voltage (AC)	230 V
Input voltage (AC), nominal values	230 V/50 Hz/4 A
Input voltage range	90 V ... 270 V
International Protection (IP class)	IP21
Level of efficiency	> 88 %
Main charge	28.4 V/28.8 V
On/Off switch	Yes
Operating temperature	-30 °C ... +60 °C
Ripple	< 3 %
Dimensions (L x W x H)	240 x 135 x 85 mm
Weight	2 kg

\*In the chosen option

Product information sheet

Product number: 0101236030

Date: 08.04.2026

Page: 3/3



## Technical Information

Switching frequency	100 kHz
Trickle charge	27.2 V/27.6 V
Type of battery	Lead acid (wet, gel, AGM)

\*In the chosen option