



## Underfloor generator UF-15000

Compact, particularly quiet, smooth-running and powerful underfloor generator with a continuous output of 15 kVA/400 V or 7 kVA/230 V, dustproof and splash-proof to IP54 with 2-pole design for a fixed speed of 3,000 1/min.

- // Output voltage: 400 V/230 V
- // Rated power: 3-phase 15 kVA/1-phase 7 kVA
- // Rated current 22 A / 30 A
- // Protection class: IP54
- // Engine rpm for generator operation 1,350 1/min

Compact, particularly quiet, smooth-running and powerful underfloor generator with a continuous output of 15 kVA/400 V or 7 kVA/230 V, dustproof and splash-proof according to IP54. Different versions are available for different types of vehicles.

The underfloor generators are driven by a power take-off, are characterised by a high overload capacity and are maintenance-free. Specifically developed and tested mounting kits are available for many vehicles. On request, we supply underfloor generators as a complete set - including socket combinations and, if required, control cabinets according to DIN 14686.

## Technical Information

<b>Generatordrehzahl</b>	3.000 1/min
<b>International Protection (IP class)</b>	IP54
<b>Polzahl</b>	2
<b>Rated Power (Alternating Current)</b>	7 kVA
<b>Rated Power (three-phase current)</b>	15 kVA
<b>Rated current (single-phase)</b>	30 A
<b>Rated current (three-phase)</b>	22 A
<b>Weight</b>	74 kg

\*In the chosen option