



## ABC Charger 2415

**24 V built-in charger for professional use with adjustable charging characteristic for gentle charging of the battery.**

- // For all types of lead batteries
- // Also available in protection class II
- // 15 selectable charging characteristics
- // Complies with DIN 14679:2024-02

The ABC 2415 charger: Optimal charging of 24 V batteries with a charging current of 15 A. In addition, a remote display or a temperature sensor (CTS) can be connected. The battery charging is fully automatic and microprocessor-monitored with selectable charging characteristic - thus an optimal and gentle charging is guaranteed.

## Technical Information

CBL connection	No*
Charging current	15 A*
Connector, AC input	Schuko plug (type F)*
Connector Temperature Sensor	Yes*
Output voltage (DC)	24 V*
Power category	600 W - 800 W*
Protection class	I*
Remote display connection	Yes*
Battery capacity	50 Ah ... 150 Ah
Building main fuse	B16 A/C16 A
Cable length, AC input	1.5 m, 0.75 mm <sup>2</sup>
Cable length, DC output	2 x 2 m, 6 mm <sup>2</sup>
Charging characteristic	15 selectable charging programmes
Complies with DIN 14679:2024-02	yes
Input frequency range	47 Hz ... 400 Hz
Input voltage (AC)	230 V
Input voltage range	90 V ... 270 V
International Protection (IP class)	IP21
Level of efficiency	> 88 %
Main charge	28.4 V/28.8 V
On/Off switch	Yes
Operating temperature	-30 °C ... +60 °C
Ripple	< 3 %
Switching frequency	100 kHz
Dimensions (L x W x H)	220 x 112 x 73 mm
Weight	1.5 kg

\*In the chosen option

Product information sheet

Product number: 0101036015

Date: 22.01.2025

Page: 3/3



## Technical Information

<b>Trickle charge</b>	27.2 V/27.6 V
-----------------------	---------------

<b>Type of battery</b>	Lead acid (wet, gel, AGM)
------------------------	---------------------------

\*In the chosen option