

Product information sheet

Product number: 1061002040

Date: 19.05.2026

Page: 1/2



XBU 630c

Independent power supply - long-lasting and powerful. The Energy Unit with XBU 630c guarantees an uninterrupted power supply. The Energy Unit is a 24 V power unit consisting of a lithium battery - the XBU 630c - and a charger. Depending on the application, the Energy Unit can be extended by various components. The heart of the system is our own development, the XBU 630c battery, which, thanks to its high capacity of 630 Ah, also supplies large consumers with energy on a permanent basis. NOTE: The XBU is only available as part of the complete Energy Unit system and is not available for individual sale. If you are interested, please contact our technical/sales department.

- // High Capacities
- // Supply of large consumers
- // Easy installation
- // Saving CO2 emissions
- // No loss of range for e-vehicles

The applications of the system are numerous, from transport cooling, to test vehicles, to applications for service technicians and fitters, a great variety is possible. Depending on the application, the system can be flexibly modified and expanded. For example, the Energy Unit can optionally be supplemented with an inverter for a 230 V output voltage, and with a DC-DC converter for a 12 V output voltage. In addition to charging via the 230 V mains supply, vehicles with combustion engines can also be charged while driving via a charge booster.

Technical Information

| | |
|-------------------------------------|-------------------------|
| Capacity | 630 Ah* |
| Charging while driving | Yes* |
| Cell chemistry | NCA |
| Charging Temperature | ± 0 °C ... + 55 °C |
| Connector | SurLok Power Connection |
| Cycle stability (80 % DoD) | > 3,000 |
| Discharging Current | 300 A |
| Discharging Temperature | - 35 °C ... + 65 °C |
| Energy Quantity | 15 kWh |
| Extractable Energy Quantity | 12,6 kWh |
| International Protection (IP class) | IP30 |
| Dimensions (L x W x H) | 805 x 311 x 429 mm |
| Weight | 90 kg |

*In the chosen option