

Product information sheet

Product number: 0101036840

Date: 27.12.2024

Page: 1/2



PWC Charger 12/100

Microprocessor-controlled battery charger for lead batteries (wet batteries, AGM/gel).

- // Two IUoU charging characteristics available
- // With charging clamps 200 A
- // Display of charging status via LED
- // Reverse polarity & short circuit protection
- // Rubber housing protection

LEAB's Professional Workshop Chargers (PWC) are high-quality battery chargers for use in workshops and service vehicles. With the PWC, all types of 12 V and 24 V lead batteries can be charged full automatically. An LED indicates the battery's state of charge. The intelligent and microprocessor-based IUoU charging characteristic ensures that the battery is charged gently and effectively.

Technical Information

Cable length	1.5 m*
Charging current	100 A*
Netzteilfunktion (Boost-PSU)	Nein*
Nominal voltage	12 V*
Battery capacity	40 Ah ... 1000 Ah
Building main fuse	B16 A/C16 A
Cable cross-section	25 mm ²
Charging characteristic	IU1U2 charging characteristic
Input frequency range	0 Hz ... 400 Hz
Input voltage (AC), nominal values	230 V/50 Hz/ 8 A
Input voltage range	90 V ... 270 V
International Protection (IP class)	IP20
Level of efficiency	> 90 %
Main charge	14.7 V/14.4 V
Operating temperature	-20 °C ... +55 °C
Protection class	I
Ripple	< 3 %
Trickle charge	13.8 V
Dimensions (L x W x H)	294 x 135 x 94.5 mm
Weight	2.2 kg

*In the chosen option