Product information sheet

Product number: 1051009002 Date: 19.04.2025 Page: 1/2





LPS II remote control

Small remote control for switching the LPS II on and off, shows the battery and operating status (LED).

- // IP21 protection class
- // Small and compact
- // Low self-consumption

The LPS II remote control is an ideal addition to the Lithium Power Supply II (LPS II). With its extra long cable, the LPS II remote control can be mounted directly in the driver's cab, for example. There, the LPS II can be switched on or off, or the emergency start function can be activated simply by pressing a button. In addition, the LPS II remote control displays the charging status of the connected LPS II to provide all important information at all times. Thanks to the practical mounting clip, the installation is done in no time.

Product information sheet

Product number: 1051009002 Date: 19.04.2025 Page: 2/2



Technical Information

Connector	M12 plug
International Protection (IP class)	IP21
Operating temperature	-20 °C +50 °C
Self-consumption	30 mA
Self-consumption (sleep mode)	2.5 mA
Supply voltage	10.5 V 24 V
Switching output (brown cable) - max. current	500 mA
Switching output (brown cable) - max. voltage (pull-up)	30 V
Wake-up output (green cable) max. current	10 mA
Dimensions (L x W x H)	50 x 75 x 15 mm
Weight	0.38 kg
*In the chosen option	

LEAB Automotive GmbH // Thorshammer 6 // 24866 Busdorf // +49 4621 97860-0 // anfrage @leab.eu // www.leab.eu