

# Champ Charger 1207 (gel/AGM)

**Small, compact and waterproof 12 V charger for universal use.**

// Compact design
// Robust: metal housing
// Waterproof: protection class IP67
// Available for all lead-acid battery types

The Champ charger is suitable for charging 12 V wet/AGM batteries. With an output voltage of 12 V and a charging current of 7 A, the compact and lightweight charger ensures particularly gentle charging of the charger thanks to the pre-programmed charging characteristic curve.

LEAB by Micropower Group

# Technical Information

| | |
|---|---|
| **Cable length, AC input** | 0.2 m* |
| **Cable length, DC output** | 1.5 m* |
| **Charging current** | 7 A* |
| **Connection DC output** | Ring terminal, M8* |
| **Connector, AC input** | DEFA* |
| **Input voltage (AC)** | 230 V* |
| **Output voltage (DC)** | 12 V* |
| **Type of battery** | Lead acid (gel, AGM)* |
| **Battery capacity** | 55 Ah ... 170 Ah |
| **Charging characteristic** | IU1U2 charging characteristic, preset |
| **Complies with DIN 14679:2024-02** | yes (except for output signal) |
| **Input frequency range** | 40 Hz ... 60 Hz |
| **Input voltage range** | 190 … 270 V |
| **International Protection (IP class)** | IP67 |
| **Level of efficiency** | ? 88 % |
| **Main charge** | 14.4 V |
| **Operating temperature** | -30 °C ... +70 °C |
| **Output voltage** | 12 V |
| **Protection class** | I |
| **Ripple** | < 3 % |
| **Switching frequency** | 100 kHz |
| **Trickle charge** | 13.8 V |
| **Dimensions (L x W x H)** | 80 x 155 x 43 mm |
| **Weight** | 0.8 kg |

*In the chosen option